

541 667

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



07 JUL 2005



(43) International Publication Date
29 July 2004 (29.07.2004)

PCT

(10) International Publication Number
WO 2004/062968 A1

(51) International Patent Classification?: B60R 13/02,
21/04, B60J 5/04

(21) International Application Number:
PCT/US2003/000419

(22) International Filing Date: 7 January 2003 (07.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): JOHN-
SON CONTROLS TECHNOLOGY COMPANY
[US/US]; 49200 Halyard Drive, Plymouth, MI 48170
(US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): BOYER, Stan, P.
[US/US]; 10432 Beechnut Lane, Zeeland, MI 49464 (US).

(74) Agent: RATHE, Todd, A.; Foley & Lardner, 777 E. Wis-
consin Avenue, 33rd Floor, Milwaukee, WI 53202-5306
(US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC,
VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,
SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: VEHICLE DOOR PANEL AND COMPONENT ASSEMBLY MOUNTED THROUGH THE PANEL



(57) Abstract: Assembly (12) includes a substrate (18) having an aperture (60) extending through the substrate (18) and having a first capping portion (62, 162, 362, 462) at least partially about the aperture (60), a skin (25) having a second capping portion (64, 164, 364, 464), at least one layer (35) between the substrate (18) and the skin (25) and a component (24) extending through the aperture (60). The first capping portion (62, 162, 362, 462) and the second capping portion (64, 164, 364, 464) cooperatively engage one another to close off the at least one compressible layer (35) between the substrate (18) and the skin (25). A method for manufacturing the panel (16) is also disclosed.

BEST AVAILABLE COPY

WO 2004/062968 A1